


AIRSTOP FLEX Adhesive Tape

To guarantee air and wind-tightness for the skin of a construction it must have the appropriate foils or panel materials providing a permanent seal at overlaps, gaps, joints and penetration points. **AIRSTOP Flex Adhesive Tape** is slightly expandable, tear-resistant, can be **plastered over** and **painted over**, has adhesive generously applied and is suitable for a variety of bonding applications.



FIELD OF APPLICATION:

- adhesion of vapour retarders and barriers
- joints of OSB and DWD (wood fibre board) panels, indoors and outdoors
- joints and connections with wood, OSB, metal...
- for adhesion to masonry use a primer if necessary

PRODUCT DATA:

Composition:	slightly expandable synthetic base material, laminated airtight, pure acrylate adhesive				
Roll width mm:	50	60	80	100	150
Roll length m :	25	25	25	25	25
Rolls/carton:	8	8	4	4	2
Thickness:	approx. 0.57 mm				
Tearing resistance:	longitudinal: > 130 N/5cm		lateral: > 80 N/5cm		
Elongation:	approx. 10%				
Resistance to temperature:	- 40°C bis + 100°C				
Resistance to ageing:	30 years				
Storage:	cool and dry				
Storability:	2 years				
UV-resistance:	max. 2 months				
Colour:	transparent white, green AIRSTOP imprint				

APPLICATION:

The materials used must be free from dust and grease and substrates must be dry and supporting. **The greater the pressure applied, the better the performance of the adhesive tape.** **AIRSTOP FLEX Adhesive Tape** has the function of sealant and not of a strong connector. The **pure acrylate** adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore this product is **extremely resistant to ageing**. Please pay attention to our Guidelines for Installation!