


AIRSTOP Sealing Plaster



To guarantee air and wind-tightness for the skin of a construction it must have the appropriate foils or panel materials providing a permanent seal at overlaps, gaps, joints and penetration points.

AIRSTOP Sealing Plaster is tear-resistant with adhesive generously applied, and is suitable for a variety of bonding applications.

FIELD OF APPLICATION:

A quick seal for larger openings e.g. blow-in openings

PRODUCT DATA:

Composition:	tear-resistant synthetic base with pure acrylate adhesive	
Roll width:	160mm	200 mm
Length:	160 mm	200 mm
Rolls à:	250 pcs.	200 pcs.
Carton contents:	4 rolls	4 rolls
Thickness:	0.3 mm	
Temperature resistance:	- 40°C to + 100°C	
Working temperature:	from - 5°C	
Resistance to ageing:	30 years	
Storage:	cool and dry	
Storability:	2 years	
Outdoor exposure:	max. 1 month	
Colour:	white with green AIRSTOP imprint	

APPLICATION:

The materials used must be free from dust and grease and substrates must be dry and supporting.

The greater the pressure applied, the better the performance of the adhesive tape.

AIRSTOP Sealing Plaster has the function of sealant and not of a firm connector. The **pure acrylate** adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore this product is **extremely resistant to ageing**.