


AIRSTOP Vapour Barrier

A transparent, extremely tear-resistant vapour barrier and airtight layer for wall, roof and ceiling constructions.



ADVANTAGES:

- transparent
- tear-resistant
- easy to install
- for floor, wall and ceiling

PRODUCT DATA:

Composition:	PP fleece with PP covering	
Roll width:	1.5 m	2.8 m
Roll length:	50 m	100 m
Roll area:	75 m ²	280 m ²
Roll weight:	7 kg	25 kg
Weight per unit area:	90 (± 10) g/m ²	
Tear strength:	longitudinal	> 160 (N/5cm)
	lateral	> 160 (N/5cm)
Elongation at maximum:	longitudinal	> 30 %
	lateral	> 30 %
Nail tear strength:	longitudinal	> 250 N
	lateral	> 240 N
Thickness:	approx. 0.2 mm	
Temperature resistance:	- 40 °C to + 80 °C	
Sd-value:	18 (± 0,5) m	
Colour:	transparent grey with green imprint	
Storage:	cool and dry	
Fire performance:	B2/ E	

APPLICATION:

AIRSTOP Vapour Barrier is attached to the substrate using a tack strip. It must be taken into consideration that only the SMOOTH SIDE can be sealed airtight. The overlap must be approx. 10 cm. All overlaps and joints must be sealed with **AIRSTOP Adhesive Tape**, **AIRSTOP Flex Adhesive Tape** or with **AIRSTOP Sealant 'SPRINT'**. We recommend the use of **AIRSTOP Cable and Pipe Sleeves** or **BUTYL Stretch Flex** for penetration points.