

AIRSTOP Window Tape

To guarantee air and wind-tightness for the skin of a construction it must have the appropriate foils or panel materials providing a permanent seal at overlaps, gaps, joints and penetration points. **AIRSTOP Window Tape** is a foldable adhesive tape with backing strips that can be pulled off individually for easy and safe sealing of the air-tight joint at windows and corner connections, and at panel butt joints in wooden constructions.

Also available with additional adhesive strips for adhesion on either side!

FIELD OF APPLICATION:

- window joints
- corner joints in wood constructions
- butt joints of panels in wooden constructions

PRODUCT DATA:

Composition:	foldable system adhesive tape with pure acrylate adhesive and three individual pull-off liners
Roll width:	60 mm
Roll length:	25 m
Carton contents:	10 rolls
Working temperature:	from - 5°C
Temperature resistance:	- 40°C to + 100°C
Resistance to ageing:	30 years
Storage:	cool and dry
Colour	white with red AIRSTOP imprint

APPLICATION:

AIRSTOP Window Tape is cut to the required length, folded to an L-shape and one side of the backing strip (1.5 or 2.5 cm) is removed. Fit **AIRSTOP** Window Tape to the corner / edge and then remove the remaining backing. The materials used must be free from dust and grease and substrates must be dry and supporting.

The greater the pressure applied, the better the performance of the adhesive tape.

AIRSTOP Window Tape has the function of sealant and not of a strong connector. The **pure acrylate** adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore this product is **extremely resistant to ageing**.